

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

SECTION 1: Identification

1.1 Product identifier

Product name **SB Speed Stripper**
Product number 610SB

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Floor-stripper

Uses advised against

All uses other than those indicated on the product label and technical data sheet.

1.3 Details of the supplier of the safety data sheet

Essential Industries, Inc.
28391 Essential Road
P.O. Box 12
Merton Wisconsin 53056
United States

Telephone: 262-538-1122
Website: www.essind.com

1.4 Emergency telephone number

Emergency information service 800-843-6174 (24 hours)

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute Tox. 4.
Acute Tox. 4.
Acute Tox. 4.
Skin Corr. 1B.
Eye Dam. 1.
Flam. Liq. 4.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **Danger**

- Pictograms



- Hazard statements

Combustible liquid.
Harmful if swallowed, in contact with skin or if inhaled.
Causes severe skin burns and eye damage.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

- Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Do not breathe dusts or mists.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin: Wash with plenty of water.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.
In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to industrial combustion plant.
Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

2.3 Other hazards

This material is combustible, but will not ignite readily.

SECTION 3: Composition/information on ingredients

3.1 Substance / Mixture

Mixture

3.2 Mixtures

Description of the mixture

Name of substance	CAS No	Wt%	Classification acc. to GHS
2-butoxyethanol	111-76-2	50 - < 75	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 4 / H227
2-aminoethanol	141-43-5	10 - < 25	Acute Tox. 4 / H302 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Flam. Liq. 4 / H227
Sodium Xylene Sulfonate	1300-72-7	1 - < 5	Acute Tox. 4 / H332 Eye Irrit. 2A / H319
Tetramethyl-5-decyne-4, 7-diol, 2, 4, 7, 9-	126-86-3	< 1	Acute Tox. 4 / H302 Eye Irrit. 2A / H319 Skin Sens. 1B / H317 STOT RE 2 / H373

Any concentration shown as a range is to protect confidentiality or is due to batch variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. For full text of abbreviations: see SECTION 16.

Date of compilation: 2024-02-07

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Self-contained breathing apparatus (SCBA). Standard protective clothing for firefighters.

Date of compilation: 2024-02-07

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it in accordance with all local, state and federal regulations.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Environmental Controls

Protect against external exposure, such as

frost

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	2-butoxyethanol	111-76-2	REL	5 (10 h)	24 (10 h)						NIOSH REL
US	2-butoxyethanol	111-76-2	TLV®	20							ACGIH® 2023
US	2-butoxyethanol	111-76-2	PEL	50	240						29 CFR 1910.1000
US	2-butoxyethanol (EGBE) (glycol monobutyl ether)	111-76-2	PEL (CA)	20	97						Cal/ OSHA PEL
US	ethanolamine	141-43-5	REL	3 (10 h)	8 (10 h)	6	15				NIOSH REL
US	ethanolamine	141-43-5	TLV®	3		6					ACGIH® 2023
US	ethanolamine	141-43-5	PEL	3	6						29 CFR 1910.1000
US	ethanolamine (2-aminoethanol)	141-43-5	PEL (CA)	3	8	6	15				Cal/ OSHA PEL

Notation

Ceiling-C
STEL

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

Notation

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear appropriate respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless
Odor	Solvent

Other safety parameters

pH (value)	9 – 11.1 (in aqueous solution: 2 wt%)
Melting point/freezing point	0 °C (32 °F)
Initial boiling point and boiling range	100 °C (212 °F)
Flash point	66.67 °C (152 °F) (c.c.)
Lower explosion limit (LEL)	not determined
Upper explosion limit (UEL)	not determined

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	<4 kPa at 20 °C
Density	0.95 g/cm ³
Vapor density	<1 (Air=1)
Solubility(ies)	not determined
VOC	74.46%

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Decomposition temperature	not determined
Viscosity	not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous combustion products: see section 5.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

- Acute toxicity estimate (ATE)

Oral	1,800 mg/kg
Dermal	1,775 mg/kg
Inhalation: vapor	17.75 mg/l/4h

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
2-butoxyethanol	111-76-2	oral	1,414 mg/kg
2-butoxyethanol	111-76-2	dermal	1,100 mg/kg
2-butoxyethanol	111-76-2	inhalation: vapor	11 mg/l/4h
2-aminoethanol	141-43-5	oral	1,089 mg/kg
Sodium Xylene Sulfonate	1300-72-7	inhalation: dust/mist	>2.4 mg/l/4h
Tetramethyl-5-decyne-4, 7-diol, 2, 4, 7, 9-	126-86-3	oral	>500 mg/kg

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
2-butoxyethanol	111-76-2	oral	LD50	1,414 mg/kg	guinea pig
2-aminoethanol	141-43-5	oral	LD50	1,089 mg/kg	rat
2-aminoethanol	141-43-5	dermal	LD50	2,504 mg/kg	rabbit
Sodium Xylene Sulfonate	1300-72-7	inhalation: dust/mist	LC50	>2,400 mg/m ³ /4h	rat
Sodium Xylene Sulfonate	1300-72-7	oral	LD50	>2,000 mg/kg	rat
Sodium Xylene Sulfonate	1300-72-7	oral	LD50	>7,000 mg/kg	rat
Sodium Xylene Sulfonate	1300-72-7	dermal	LD50	>2,000 mg/kg	rabbit
Tetramethyl-5-decyne-4, 7-diol, 2, 4, 7, 9-	126-86-3	oral	LD50	>500 mg/kg	rat
Tetramethyl-5-decyne-4, 7-diol, 2, 4, 7, 9-	126-86-3	dermal	LD50	>2,000 mg/kg	rat

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
2-butoxyethanol	111-76-2	3	

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butoxyethanol	111-76-2	LC50	1,474 mg/l	fish	96 h
2-butoxyethanol	111-76-2	EC50	1,550 mg/l	aquatic invertebrates	48 h
2-butoxyethanol	111-76-2	ErC50	1,840 mg/l	algae	72 h
2-aminoethanol	141-43-5	LC50	349 mg/l	fish	96 h
2-aminoethanol	141-43-5	EC50	27.04 mg/l	aquatic invertebrates	48 h
2-aminoethanol	141-43-5	ErC50	2.8 mg/l	algae	72 h
Sodium Xylene Sulfonate	1300-72-7	LC50	1,766 mg/l	daphnia	48 h
Sodium Xylene Sulfonate	1300-72-7	LC50	7,960 mg/l	fathead minnow (Pimephales promelas)	96 h

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium Xylene Sulfonate	1300-72-7	EC50	>1,020 mg/l	daphnia	48 h
Tetramethyl-5-decyne-4,7-diol, 2, 4, 7, 9-	126-86-3	LC50	42 mg/l	fish	96 h
Tetramethyl-5-decyne-4,7-diol, 2, 4, 7, 9-	126-86-3	EC50	91 mg/l	aquatic invertebrates	48 h
Tetramethyl-5-decyne-4,7-diol, 2, 4, 7, 9-	126-86-3	ErC50	39 mg/l	algae	48 h

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butoxyethanol	111-76-2	EC50	297 mg/l	aquatic invertebrates	21 d
2-aminoethanol	141-43-5	EC50	2.5 mg/l	aquatic invertebrates	21 d
Tetramethyl-5-decyne-4,7-diol, 2, 4, 7, 9-	126-86-3	EC50	840 mg/l	microorganisms	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07


Remarks

Dispose of contents/container in accordance with local/regional/national/international regulations. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Dispose of contents/container to an authorized waste treatment facility. Waste should not be disposed of by release to sewers. Avoid release to the environment. Empty container and inner liner may contain product residues. Ideally, waste should be prevented and what cannot be prevented should be re-used, recycled and recovered as much as feasible.


SECTION 14: Transport information

Information for each of the UN Model Regulations


Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1719, Caustic alkali liquids, n.o.s., (2-aminoethanol), 8, III
Danger label(s)	8
	
ERG No	154
Limited quantities (LQ)	5 L

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration	UN1719, CAUSTIC ALKALI LIQUIDS, N.O.S., (2-aminoethanol), 8, III
Marine pollutant	-
Danger label(s)	8
	
Limited quantities (LQ)	5 L
Segregation group	18 - Alkalis

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration	UN1719, Caustic alkali liquids, n.o.s., (2-aminoethanol), 8, III
Danger label(s)	8
	
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations

Toxic Substance Control Act (TSCA) all ingredients are listed (ACTIVE) or exempt from listing

DSL/NDSL (Canada) all ingredients are listed on or exempt from the DSL

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
2-butoxyethanol		R - (OCH ₂ CH ₂) _n - OR' Where: n = 1, 2, or 3; R = alkyl C7 or less; or R = phenyl or alkyl substituted phenyl; R' = H or alkyl C7 or less; or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate.	1995-01-01

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
diethanolamine	111-42-2		cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on the tested mixture and/or formulator knowledge.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Date of compilation: 2024-02-07

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.