

www.essind.com

**X-Coat™**  
patented nano-zinc  
technology

**NANO 22  
PLUS**



**Extreme  
Performance Coating**



**251FF**

**Performance Coating**

## Features

- Incorporates our patented nano-zinc technology for more thoroughly and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
  - Lay-down gloss
  - Durability
  - Soil resistance
  - Gloss build
  - Mark resistance
  - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- High solids formula offers greater protection with fewer coats.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula - meets California's new 1% VOC Regulation.
- Fast-drying - 20-30 minutes under normal conditions.
- Slip-resistant - Meets ASTM D2047




## Properties

**Type:** Acrylic Emulsion  
**Form:** Opaque Liquid  
**Odor:** Bland  
**Color:** Milky White  
**Film Clarity:** Clear

**pH:** 7.0 - 8.0  
**Weight Per Gallon:** 8.56 Lbs.  
**Storage Stability:** Minimum 1 Year  
**Freeze/Thaw:** Protect From Freezing  
**V.O.C.:** 0.57%

Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to Safety Data Sheet.

**ESSENTIAL®  
INDUSTRIES**

P.O. Box 12  
 Merton, Wisconsin 53056  
 Phone: (262) 538-1122  
 www.essind.com

© 2025 Essential Industries, Inc. B0625  
 Lit. # LT-90000S0251FF