

www.essind.com

X-CoatTM NANO 22

patented nano-zinc technology



86FF

Performance Coating

Extreme

Features

- Incorporates our patented nano-zinc technology for more thoroughly and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
 - Lay-down gloss
 - Durability
 - Soil resistance
 - Gloss build
 - Mark resistance
 - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- High solids formula offers greater protection with fewer coats.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula - meets California's new 1% VOC Regulation.
- Fast-drying - 15-20 minutes under normal conditions.
- Slip-resistant - UL-classified

Properties

Type: Acrylic Emulsion
Form: Opaque Liquid
Odor: Bland
Color: Milky White
Film Clarity: Clear

pH: 7.0 - 7.9
Weight Per Gallon: 8.65 Lbs.
Storage Stability: Minimum 1 Year
Freeze/Thaw: Protect From Freezing
V.O.C.: 0.7%

Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to Safety Data Sheet.

ESSENTIAL[®]
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2024 Essential Industries, Inc. B0524
Lit. # LT-90000S0086FF